

Fire ratings are available in most JELD-WEN® door product lines. There may be restrictions based on size and regional availability, so please use this sheet as a reference and discuss further with your JELD-WEN supplier. All door slabs must be used with fire-rated door systems for true fire protection. A door system consists of the door slab, frame, hardware and components.

Exterior Doors				
Product Type	Ratings	Features	Models	
Custom Wood Doors	20-minutes, 45-minutes, 60-minutes, 90-minutes	20-minutes	<ul style="list-style-type: none"> • Fire-rated solid core • 1-3/4" doors 	Available with all-panel doors.
		45-minutes	<ul style="list-style-type: none"> • FyreWerks core • 1-3/4" doors 	
		60-minutes	<ul style="list-style-type: none"> • FyreWerks core • 1-3/4" doors 	
		90-minutes	<ul style="list-style-type: none"> • FyreWerks core • 1-3/4" doors 	
Fiberglass Doors	20-minutes	20-minutes	<ul style="list-style-type: none"> • Fire-rated solid core • 1-3/4" doors • Laminated Veneer Lumber (LVL) stiles & rails • LFI-capped top rail and PVC capped stiles and bottom rails 	Available with all-panel doors: Architectural Fiberglass Doors Design-Pro Fiberglass Doors Smooth-Pro Fiberglass Doors
Steel Doors	20-minutes, 45-minutes, 60-minutes, 90-minutes	20-minutes	<ul style="list-style-type: none"> • Wood edge 	Available with all-panel doors: Contours™ Energy Saver® 2-Panel Designs
		45-minutes	<ul style="list-style-type: none"> • Steel edge 	
		60-minutes	<ul style="list-style-type: none"> • Steel edge 	
		90-minutes	<ul style="list-style-type: none"> • Steel edge 	
Interior Doors				
Product Type	Ratings	Features	Models	
Custom Wood Doors	20-minutes, 45-minutes, 60-minutes, 90-minutes	20-minutes	<ul style="list-style-type: none"> • Fire-rated solid core • 1-3/4" doors 	Available with all-panel doors.
		45-minutes	<ul style="list-style-type: none"> • FyreWerks core • 1-3/4" doors 	
		60-minutes	<ul style="list-style-type: none"> • FyreWerks core • 1-3/4" doors 	
		90-minutes	<ul style="list-style-type: none"> • FyreWerks core • 1-3/4" doors 	
Custom Carved Doors	20-minutes	20-minutes	<ul style="list-style-type: none"> • Fire-rated solid core • 1-3/4" doors 	Available with all raised panel doors.
Molded Doors	20-minutes, 45-minutes, 60-minutes	20-minutes	<ul style="list-style-type: none"> • Wood-based panel core • 1-3/4" doors 	Available in all standard models except Impression™ Mirror doors. Craftsman III™ is available with a 20-minute fire rating only.
		45-minutes	<ul style="list-style-type: none"> • Solid mineral core • 1-3/4" doors 	
		60-minutes	<ul style="list-style-type: none"> • Solid mineral core • 1-3/4" doors 	
Flush Doors	20-minutes, 45-minutes, 60-minutes, 90-minutes	20-minutes	<ul style="list-style-type: none"> • Wood-based panel core • 1-3/4" doors 	Available in all models.
		45-minutes	<ul style="list-style-type: none"> • Wood-based panel core or mineral core • 1-3/4" doors 	
		60-minutes	<ul style="list-style-type: none"> • Wood-based panel core or mineral core • 1-3/4" doors 	
		90-minutes	<ul style="list-style-type: none"> • Solid mineral core • 1-3/4" doors 	