

The performance information listed is for new products and is intended to be used for reference only, and is not complete. Depending on the components, accessories, and options chosen, the actual rating could vary. Confirm ratings for specific products with your supplier or JELD-WEN sales representative.

JELD-WEN Fiberglass Exterior Doors	Glazing (nominal) Ext -airgap - int	Thickness	STC	OITC
Fiberglass Textured Skin (6 panel)	None	1.69	25	22
Fiberglass Textured Skin (Flush)	None	1.69	25	22
Fiberglass Text. Skin (Full-lite Cutout)	1" ODL	1.69	30	26
Fiberglass Text. Skin (Full-lite Cutout)	0.5" ODL	1.69	29	26
JELD-WEN Steel Exterior Doors	Glazing (nominal) Ext -airgap - int	Thickness	STC	OITC
Gladiator W/E (6 panel)	None	1.75	22	22
Gladiator W/E (Flush)	None	1.75	19	21
Gladiator W/E (Full-lite Cutout)	1" ODL	1.75	26	25
Gladiator W/E (Full-lite Cutout)	0.5" ODL	1.75	26	25
Energy Saver W/E (6 panel)	None	1.75	23	22
Energy Saver W/E (Flush)	None	1.75	20	22
Energy Saver W/E (Full-lite Cutout)	1" ODL	1.75	26	25
Energy Saver W/E (half-lite Cutout)	1" ODL	1.75	25	24
Energy Saver W/E (Full-lite Cutout)	0.5" ODL	1.75	27	25
Energy Saver W/E (half-lite Cutout)	0.5" ODL	1.75	25	24
Energy Saver S/E (6 panel)	None	1.75	22	22
Energy Saver S/E (Flush)	None	1.75	22	23
Energy Saver S/E (Full-lite Cutout)	1" ODL	1.75	28	25
Energy Saver S/E (half-lite Cutout)	1" ODL	1.75	27	24
Energy Saver S/E (Full-lite Cutout)	0.5" ODL	1.75	28	25
Energy Saver S/E (half-lite Cutout)	0.5" ODL	1.75	26	24
Contour W/E (half-lite Cutout)	1" ODL	1.75	24	23
Contour W/E (half-lite Cutout)	0.5" ODL	1.75	24	23
Finishield Flush Skin	None	1.75	20	22