

The performance information listed is intended to be used for reference only and is not complete. Depending on the components, accessories, and options chosen, the actual rating could vary. Confirm ratings for specific products with your supplier or JELD-WEN sales representative.

Product	AAMA/WDMA				
	101 / I.S. 2 / A440-05				
	Config.	Max Size Tested	Hallmark Certified Performance Rating (DP)	Water Performance (psf)	Air Performance (cfm/ft2)
Clad Casement	Single Unit w/ sash limiter	36x72, 41x64	R35 standard	5.25	< 0.1
	Single	36x72	R50	7.50	< 0.1
Clad Casement In Sash Fixed	Single Unit	56x72	R35 standard	7.50	< 0.1
	Single Unit	56x72	R50 standard	7.50	< 0.1
Clad Awning	Single Unit	48x32	R35 standard all sizes	5.25	< 0.1
	Single Unit	40x30	R50 standard some sizes	7.50	< 0.1
Clad Double-Hung	Single Unit	37x64, 33x76	R35 standard	5.25	< 0.3
	Single Unit	37x76	R50	7.00	< 0.2
Clad Double-Hung Transom	Single Unit	37 3/8x24	R35 standard all sizes	5.25	< 0.1
	Single Unit	37x24	R50	7.50	< 0.1
Clad Double-Hung Picture	Single Unit	84x84	R50 standard all sizes	7.50	< 0.1
Clad Direct Set	Single Unit	60x76	R35 standard all sizes	5.25	< 0.1
	Single Unit	60x76	R50 optional all sizes	7.50	< 0.1
Clad Sliding Patio Door	2 Panel	Up to 82" height (6'11")	DP35 standard	5.25	< 0.1
	2 Panel	Up to 82" height (6'11")	DP 50 option	7.50	< 0.1
	2 Panel	Up to 95.5" height (8'0")	DP 35 standard	5.25	< 0.1
	2 Panel w/ Transom	All sizes	DP 35 standard	5.25	< 0.1
	3 Panel	All sizes	DP 35 standard	5.25	< 0.1
	3 Panel w/ Transom	All sizes	DP 35 standard	5.25	< 0.1
	3 Panel w/ Twin Transom	All sizes	DP 25 standard	3.75	< 0.1
Clad Sliding Patio Door Sidelight / Fixed Panel	1 Panel	All sizes	DP 35 standard	5.25	< 0.1
	1 Panel	All sizes	DP 50 option	7.50	< 0.1
	1 Panel w/ Transom	All sizes	DP 35 standard	5.25	< 0.1