

The performance information listed is for new products and is intended to be used for reference only, and is not complete. Depending on the components, accessories, and options chosen, the actual rating could vary. Confirm ratings for specific products with your supplier or JELD-WEN sales representative.

JELD-WEN Interior Doors	Glazing (nominal) Ext -airgap - int	Thickness	STC	OITC
Bostonian Procore (6 panel)	None	1.375	30	28
Bostonian Hollow Core	N/A	1 - 3/8"	26	19
Colonial 60 min. Fire Rated Door (6 panel)	None	1.75	29	29
Colonial 20 min. Fire Rated Door (6 panel)	None	1.75	30	29
Colonial Hollow Core (6 panel)	None	1.375	25	20
Colonial Procore (6 panel)	None	1.375	30	29
Camden ProCore	N/A	1 - 3/8"	30	29
Camden Hollow Core	N/A	1 - 3/8"	27	21
RockPort ProCore	N/A	1 - 3/8"	30	28
RockPort Hollow Core	N/A	1 - 3/8"	25	20
Flush 60 min. Fire Rated Door	None	1.75	34	31
Flush 20 min. Fire Rated Door	None	1.75	32	30
Flush Hollow Core	None	1.375	24	19
Flush Procore	None	1.375	30	29
Custom Carved w/ Honeycomb core (in a door system)	None	1.375	25	25
Custom Carved w/ Honeycomb core (panel only)	None	1.375	33	30
Custom Carved fire-rated / Celotex core (in a door system)	None	1.75	27	27
Custom Carved fire-rated / Celotex core (panel only)	None	1.75	32	30