

The performance information listed is for new products and is intended to be used for reference only, and is not complete. Depending on the components, accessories, and options chosen, the actual rating could vary. Confirm ratings for specific products with your supplier or JELD-WEN sales representative. Products subject to regional availability. Please visit <http://www.jeld-wen.com/windows> to verify which products are available in your area.

Product	AAMA/WDMA					
	101 / I.S. 2 / A440-05					
	Regional Availability E = Eastern US C = Central US W = Western US	Config.	Performance Grade and Class (DP) Rating	Max Size Tested	Water Performance (psf)	Air Performance (cfm/ft2)
Casement	W	Single Unit	C30	36x72	4.50	< 0.1
	W	Single Unit	C50	36x72	7.50	< 0.1
	W	Single Unit with Transom	C30	36x61	4.50	< 0.1
Awning	W	Single Unit	C30	60x36	4.50	< 0.1
	W	Single Unit	C50	60x36	7.50	< 0.1
Single-Hung	W	Single Unit	R20	46x96	3.00	< 0.3
Horizontal Slider	W	Single Unit	C30	72x60	4.50	< 0.2
	W	Single Unit	LC25	84x56	3.75	< 0.2
	W	Single Unit	R20	96x72	3.00	0.1
	W	XOX	C30	108x60	4.50	< 0.2
	W	XOX	R20	144x72	3.00	< 0.1
Picture	W	Single Unit	C40	93x85	6.00	< 0.1
	W	Twin	LC25	93x56	3.75	< 0.1
Sliding Patio Door	W	XO	R20	96x96	3.00	< 0.3
	W	XXO	R20	180x120	3.00	< 0.3
	W	OXXO	R20	192x96	3.00	< 0.3