

The performance information listed is for new products and is intended to be used for reference only, and is not complete. Depending on the components, accessories, and options chosen, the actual rating could vary. Confirm ratings for specific products with your supplier or JELD-WEN sales representative. Products subject to regional availability. Please visit <http://www.jeld-wen.com/windows> to verify which products are available in your area.

| Product | | | | | | | | | | | |
|-------------------|---------------------|--------|-------------------|-------------------------------------|-----------------------------------|-----------|-------------------------|-------------------------|-------------------------|------------|------------|
| | Impact / Non-Impact | Config | Max Size | Minimum Glass | Design Pressure (DP) Rating (+/-) | Sill Type | Wind Velocity mph (+/-) | 2007 Florida Approval # | 2004 Florida Approval # | DADE NOA # | TDI # |
| Single-Hung | Non-Impact | | 52-1/8" x 75" | Temp 1/8" insulated | R70 | riser | 165 | 10948.2 | 9354.2 | | |
| | Non-Impact | | 36" x 75" | 1/8" insulated | R65 | riser | 159 | 10948.1 | 9354.3 | | |
| | Non-Impact | | 47-1/2" x 63-1/2" | 1/8" insulated | R65 | riser | 159 | 10948.3 | 9354.1 | | |
| | Impact | | 52-1/8" x 75" | 5/16" Lam single glaze (S/P) | 50 | riser | 140 | 11599.4 | 9664.2 | | |
| | Impact | | 52-1/8" x 75" | 5/16" Lam (S/P) - 3/16" insulated | 50 | riser | 140 | 11599.3 | 10034.3 | | |
| | Impact | | 54" x 74" | 5/16" Lam (S/P) - 3/16" insulated | 50 (+50/-60) | riser | +140/-153 | | 10034.4 | | win-761 |
| | Impact | | 54" x 74" | 5/16" Lam (S) - 3/16" insulated | 50 (+50/-60) | riser | +140/-153 | 11120.2 | 7958.1 | 06-0407.02 | win-761 |
| | Impact | | 36" x 72" | 5/16" Lam (S) - 3/16" insulated | 65 (+65/-70) | riser | +159/-165 | 11120.3 | 7958.1 | 06-0407.02 | |
| Horizontal Roller | Non-Impact | OX/XO | 74" x 54" | 3/16" insulated | R50 | std | 140 | 10953.1 | 8425.1 | | |
| | Impact | OX/XO | 74" x 54" | 5/16" Lam single glaze (S/P) | 50 (+50/-60) | std | +140/-153 | 10695.1 | 10033.3 | | |
| | Impact | OX/XO | 74" x 54" | 5/16" Lam (S) - 3/16" insulated | 50 (+50/-60) | std | +140/-153 | | 7959.2 | 06-0407.03 | win-760 |
| | Impact | OX/XO | 74" x 54" | 5/16" Lam (S/P) - 3/16" insulated | 50 (+50/-60) | std | +140/-153 | 10695.2 | 10033.3 | | win-760 |
| Fixed | Non-Impact | | 74" x 75" | Temp 3/16" single glaze & insulated | C80 | std | 177 | 10937.4 | 9034.5 | | |
| | Non-Impact | | 52-1/8" x 62" | 3/16" single glaze & insulated | R65 | std | 159 | 10937.5 | | | |
| | Non-Impact | | 48" x 74" | 3/16" insulated | R70 | std | 165 | 10937.3 | 8774.1 | | |
| | Non-Impact | | 48" x 48" | 1/8" insulated | R50 | std | 140 | 10937.1 | 10032.4 | | |
| | Non-Impact | | 36" x 62" | 1/8" insulated | R50 | std | 140 | 10937.2 | 10032.5 | | |
| | Impact | | 52-1/8" x 75" | 7/16" Lam single glaze (S/P) | R50 | std | 140 | | 8401 | | |
| | Impact | | 52-1/8" x 75" | 7/16" Lam single glaze (S) | R50 | std | 140 | 11117.7 | | 06-1017.04 | |
| | Impact | | 54" x 74" | 5/16" Lam (S/P) - 3/16" insulated | R50 | std | 165 | 11598.6 | 10032.7 | | |
| | Impact | | 54" x 74" | 5/16" Lam (S) - 3/16" insulated | R50 | std | 165 | 11117.5 | | 06-0407.01 | |
| | Impact | GEO | | 54" x 74" | 7/16" Lam single glaze (S) | R50 | std | 140 | 11117.6 | | 06-1017.04 |

The performance information listed is for new products and is intended to be used for reference only, and is not complete. Depending on the components, accessories, and options chosen, the actual rating could vary. Confirm ratings for specific products with your supplier or JELD-WEN sales representative. Products subject to regional availability. Please visit <http://www.jeld-wen.com/windows> to verify which products are available in your area.

| Product | | | | | | | | | | | |
|----------------|---------------------|--------|-------------------|--------------------------------------|-----------------------------------|-----------|-------------------------|-------------------------|-------------------------|------------|---------|
| | Impact / Non-Impact | Config | Max Size | Minimum Glass | Design Pressure (DP) Rating (+/-) | Sill Type | Wind Velocity mph (+/-) | 2007 Florida Approval # | 2004 Florida Approval # | DADE NOA # | TDI # |
| | Impact | GEO | 54" x 74" | 5/16" Lam (S/P) - 3/16" insulated | R50 | std | 140 | | 10032.6 | | |
| | Impact | GEO | 54" x 74" | 5/16" Lam (S) - 3/16" insulated | R50 | std | 140 | 11117.5 | 7939.1 | 06-0407.01 | |
| | Impact | | 52-1/8" x 75" | 5/16" Lam (S/P) - 3/16" insulated | R50 | std | 140 | 11598.1 | 8401.2 | | win-782 |
| | Impact | | 52-1/8" x 75" | 5/16" Lam (S) - 3/16" insulated | R50 | std | 140 | 11117.7 | | 06-1017.04 | win-782 |
| Casement | Non-Impact | X | 35-1/2" x 71-1/2" | 3/16" insulated | C50 | std | 140 | 10952.1 | 6259.6 | | |
| | Impact | X | 35-1/2" x 71-1/2" | 5/16" Lam (S/P) - 1/8" insulated | R50 | std | 140 | 10336.1 | 6259.7 | | |
| | Impact | X | 35-1/2" x 71-1/2" | 5/16" Lam (S) - 1/8" insulated | R50 | std | 140 | 11114.1 | | 06-0504.03 | |
| | Impact | X | 35-1/2" x 71-1/2" | 5/16" Lam single glaze (S/P) | R50 | std | 140 | 10336.2 | 6259 | | |
| | Impact | X | 35-1/2" x 71-1/2" | 5/16" Lam single glaze (S) | R50 | std | 140 | | | 07-0314.02 | |
| Casement Fixed | Impact | O | 35-1/2" x 71-1/2" | 5/16" Lam single glaze (S) | R50 | std | 140 | 11117.4 | | 07-0314.03 | |
| | Impact | O | 35-1/2" x 71-1/2" | 5/16" Lam single glaze (S/P) | R50 | std | 140 | 11598.4 | 10032.8 | | |
| | Impact | O | 35-1/2" x 71-1/2" | 5/16" Lam (S) - 1/8" insulated | R50 | std | 140 | 11117.4 | | 07-0314.03 | win-940 |
| | Impact | O | 35-1/2" x 71-1/2" | 5/16" Lam (S/P) - 1/8" insulated | R50 | std | 140 | 11598.2 | 8401.1 | | win-940 |
| Awning | Non-Impact | X | 47-1/2" x 31-1/2" | 1/8" insulated | R50 | std | 140 | 10942.1 | 8212.1 | | |
| | Impact | X | 47-1/2" x 31-1/2" | 5/16" Lam single glaze (S) | R50 | std | 140 | 11113.1 | | 07-0612.04 | |
| | Impact | X | 47-1/2" x 31-1/2" | 5/16" Lam single glaze (S/P) | R50 | std | 140 | 11530.1 | 8399.1 | | |
| | Impact | X | 47-1/2" x 31-1/2" | 5/16" Lam (S) - 1/8" insulated | R50 | std | 140 | 11113.2 | 8212.2 | 07-0104.06 | |
| Swinging Door | Non-Impact | X | 36-1/4" x 95-1/2" | Temp 3/16" single glaze & insulated | R50 | std | 140 | 10972.1 | 9045.1 | | |
| | Impact | X | 36-1/4" x 95-1/2" | 5/16" Lam single glaze (S) | 50 | std | 140 | 11812.2 | 8402.1 | | |
| | Impact | X | 36-1/4" x 95-1/2" | 5/16" Lam single glaze (S) | 50 | std | 140 | | | | |
| | Impact | X | 36-1/4" x 95-1/2" | 5/16" Lam (S) - Temp 3/16" insulated | 50 | std | 140 | 11112.1 | | 06-0710.16 | |
| | Impact | X | 36-1/4" x 95-1/2" | 5/16" Lam (S) - Temp 3/16" insulated | 50 | std | 140 | 11812.1 | 8402.2 | | |



Premium Atlantic Vinyl - Venice

The performance information listed is for new products and is intended to be used for reference only, and is not complete. Depending on the components, accessories, and options chosen, the actual rating could vary. Confirm ratings for specific products with your supplier or JELD-WEN sales representative. Products subject to regional availability. Please visit <http://www.jeld-wen.com/windows> to verify which products are available in your area.

| Product | | | | | | | | | | | |
|----------------------|---------------------|-----------------------------|--------------------|--|-----------------------------------|-----------|-------------------------|-------------------------|-------------------------|------------|--------|
| | Impact / Non-Impact | Config | Max Size | Minimum Glass | Design Pressure (DP) Rating (+/-) | Sill Type | Wind Velocity mph (+/-) | 2007 Florida Approval # | 2004 Florida Approval # | DADE NOA # | TDI # |
| Swinging French Door | Non-Impact | XX | 71-1/2" x 95-1/2" | Temp 3/16" single glaze & insulated | R35 | std | 117 | 10972.2 | 9045.2 | | |
| | Impact | XX | 71-1/2" x 95-1/2" | 5/16" Lam (S) - Temp 3/16" insulated | 50 | std | 140 | 11812.3 | 9045.3 | | |
| | Impact | XX | 71-1/2" x 95-1/2" | 5/16" Lam (S) - Temp 3/16" insulated | 50 | std | 140 | 11112.2 | | 06-0710.16 | |
| | Impact | 3/0 x 8/0 Sidelite | 36-1/4" x 95-1/2" | 7/16" Lam (S) - Temp 3/16" insulated | 50 | std | 140 | 11812.5 | 10032.1 | | |
| | Impact | 6/0 x 4/0 Transom | 73-3/8" x 47-1/2" | 7/16" Lam (S) - Temp 3/16" insulated | 50 | std | 140 | 11812.5 | 10032.2 | | |
| | Impact | XX w/ Sidelite and Transom | 149" x 146-1/4" | 7/16" Lam (S) - Temp 3/16" insulated | 50 | std | 140 | 11812.5 | 9045.4 | | |
| | Impact | 3/0 x 8/0 Sidelite | 36-1/4" x 95-1/2" | 7/16" Lam (S) - Temp 3/16" insulated | 50 | std | 140 | | | | |
| | Impact | 6/0 x 4/0 Transom | 73-3/8" x 47-1/2" | 7/16" Lam (S) - Temp 3/16" insulated | 50 | std | 140 | | | | |
| | Impact | XX w/ Sidelite and Transom | 149" x 146-1/4" | 7/16" Lam (S) - Temp 3/16" insulated | 50 | std | 140 | | | | |
| Sliding Patio Door | Non-Impact | x0, ox, xx, oxo, oxxo, xxxx | 190-5/8" x 95-1/2" | Temp 3/16" insulated | C50 | std | 140 | 10976.3 | 7581.2 | | |
| | Impact | x0, ox, xx, oxo, oxxo, xxxx | 190-5/8" x 95-1/2" | 7/16" Lam single glaze (S) | 50 | std | 140 | 10973.1 | 10035.1 | | |
| | Impact | x0, ox, xx, oxo, oxxo, xxxx | 142-5/8" x 79-1/2" | 7/16" H/S Lam (S) - Temp 3/16" insulated | 65 | riser | 159 | | 7040.4 | | DR-246 |
| | Impact | x0, ox, xx, oxo, oxxo, xxxx | 142-5/8" x 79-1/2" | 7/16" H/S Lam (S) - Temp 3/16" insulated | 65 | riser | 159 | | | | DR-246 |
| | Impact | x0, ox, xx, oxo, oxxo, xxxx | 190-5/8" x 95-1/2" | 7/16" Lam (S) - Temp 3/16" insulated | 50 | std | 140 | 10973.9 | 7581.1 | | DR-246 |
| | Impact | x0, ox, xx, oxo, oxxo, xxxx | 190-5/8" x 95-1/2" | 7/16" Lam (S) - Temp 3/16" insulated | 50 | std | 140 | 11109.3 | 7962.1 | 08-0206.02 | DR-246 |
| | Impact | All Configs w/ Transom | 190-5/8" x 146" | 7/16" Lam (S) - Temp 3/16" insulated | 50 | std | 140 | 10973.8 | 8776.1 | | DR-246 |
| | Impact | 8/0 x 4/0 Transom | 94-3/16" x 47-1/2" | 7/16" Lam (S) - Temp 3/16" insulated | 50 | std | 140 | 10973.8 | 10032.3 | | DR-246 |

The performance information listed is for new products and is intended to be used for reference only, and is not complete. Depending on the components, accessories, and options chosen, the actual rating could vary. Confirm ratings for specific products with your supplier or JELD-WEN sales representative. Products subject to regional availability. Please visit <http://www.jeld-wen.com/windows> to verify which products are available in your area.

| Product | | | | | | | | | | | |
|---------|---------------------|--------|----------|---------------|-----------------------------------|-----------|-------------------------|-------------------------|-------------------------|------------|------------|
| | Impact / Non-Impact | Config | Max Size | Minimum Glass | Design Pressure (DP) Rating (+/-) | Sill Type | Wind Velocity mph (+/-) | 2007 Florida Approval # | 2004 Florida Approval # | DADE NOA # | TDI # |
| Mullion | Non-Impact | | 1x3 tube | | 75 | | 171 | 8398 | 7922 | | |
| | Non-Impact | | 1x4 tube | | 75 | | 171 | 8398 | 7922 | | |
| | Impact | | 2x5 tube | Swing Doors | | | | 10973.8 | 10032 | | |
| | Impact | | 2x5 tube | Sliding Doors | | | | 11812.5 | | | |
| | Impact | | 1x3 tube | | | varies | | | 11870.1 | | 07-0629.03 |
| | Impact | | 1x4 tube | | | 50 | | 140 | 11870.1 | 8398 | 07-0629.03 |

All products above tested to Wind Zone 4 and Exposure A-B-C-D

RELIABILITY for real life®



Rev. 4/20/09