

The performance information listed is for new products and is intended to be used for reference only, and is not complete. Depending on the components, accessories, and options chosen, the actual rating could vary. Confirm ratings for specific products with your supplier or JELD-WEN sales representative. Products subject to regional availability. Please visit <http://www.jeld-wen.com/windows> to verify which products are available in your area.

Product	AAMA/WDMA						
	Regional Availability = Eastern US = Central US W = Western US	E C	Config.	Performance Grade and Class (DP) Rating	Max Size Tested	Water Performance (psf)	Air Performance (cfm/ft2)
Casement	E		Single Unit	R50	36x72	7.50	< 0.1
	E		Twin	R20	72x72	3.00	< 0.1
Awning	E		Single Unit	R50	48x36	7.50	< 0.1
Double-Hung	E		Single Unit	R20	48x77	3.00	< 0.3
	E		Single Unit	R50 option	38x74, 42x57	7.50	< 0.1
	E		Twin	R50	84x57	7.50	< 0.1
	E		Triple	R20	120x60	3.00	< 0.2
	E		Triple	R50	114x74	7.50	< 0.3
	E		XOX	R20	98x77	3.00	< 0.2
Picture	E		Single Unit	R20	96x71	3.00	< 0.1
Sliding Patio Door	E		XO	R20	71x80	3.00	< 0.3
	E		XO	R20	95.5x95.5	3.00	< 0.1
	E		XO w/ transom	R20	71x92	3.00	< 0.3