

The performance information listed is for new products and is intended to be used for reference only, and is not complete. Depending on the components, accessories, and options chosen, the actual rating could vary. Confirm ratings for specific products with your supplier or JELD-WEN sales representative. Products subject to regional availability. Please visit <http://www.jeld-wen.com/windows> to verify which products are available in your area.

Product	AAMA/WDMA					
	101 / I.S. 2 / A440-05					
	Regional Availability E = Eastern US C = Central US W = Western US	Config.	Performance Grade and Class (DP) Rating	Max Size Tested	Water Performance (psf)	Air Performance (cfm/ft <sup>2</sup> )
<b>Casement</b>	W	Single Unit	C30	36x60	4.50	< 0.1
	W	Single Unit	LC25	36x72	3.75	< 0.2
<b>Stationary Casement</b>	W	Single Unit	C30	60x72	4.50	< 0.1
<b>Awning</b>	W	Single Unit	LC25	72x36	3.00	< 0.1
<b>Single-Hung</b>	W	Single Unit	LC25	48x96	3.75	< 0.1
<b>Double-Hung</b>	W	Single Unit	R20	48x75.5	3.00	0.30
<b>Roller</b>	W	Single Unit	LC25	72x60	3.75	< 0.3
	W	XOX	LC25	120x60	3.75	< 0.3
<b>Picture</b>	W	Single Unit	C30	72x72	4.5 psf	< 0.1
	W	Single Unit	LC25	96x72	3.75	< 0.1
<b>Sliding Patio Door</b>	W	OX	R20	96x96, 120x80	3.00	< 0.2
	W	OXO	R20	180x80, 144x96	3.00	< 0.1