

The performance information listed is intended to be used for reference only and is not complete. Depending on the components, accessories, and options chosen, the actual rating could vary. Confirm ratings for specific products with your supplier or JELD-WEN sales representative.

Product	AAMA/WDMA				
	101 / I.S. 2 / A440-05				
	Config.	Max Size Tested	Hallmark Certified Performance Rating (DP)	Water Performance (psf)	Air Performance (cfm/ft <sup>2</sup> )
Clad Casement	Single Unit	36x84	C35 standard all sizes	5.25	< 0.2
	Single Unit	36x84	C50 optional all sizes	5.25	< 0.2
	Single Unit	36x72	C65 optional some sizes	9.75	< 0.1
Clad Radius Casement	Single Unit		C35 standard all sizes		
	Single Unit	30x84	C50 optional all sizes	7.5	< 0.1
Clad Casement Fixed	Single Unit	72x84	C35 standard all sizes	5.25	< 0.1
	Single Unit	72x84, 60x72	C50 optional all sizes	7.5	< 0.1
	Single Unit	42x54	C65 optional some sizes	9.75	0
Clad French Casement	Single Unit	56x72	R20 standard some sizes	5.25	< 0.1
	Single Unit	56x54	R30 standard some sizes	5.25	< 0.1
Clad Push-Out Casement	Single Unit	36x72	C50 standard all sizes	7.5	< 0.2
Clad Push-Out Casement Fixed	Single Unit	60x72	C80 standard all sizes	12	< 0.1
Clad Awning	Single Unit	60x48	C35 standard all sizes	5.25	< 0.1
	Single Unit	48x36	C50 optional some sizes	7.5	< 0.1
	Single Unit	36x24	C65 optional some sizes	9.75	< 0.1
Clad Double-Hung	Single Unit	37x96 (also tested - 49x77, 45x80, 41x88)	LC35 standard all sizes	5.25	< 0.1
	Single Unit	49x77 (also tested - 41x88, 45x80, 37x96)	LC40 optional all sizes	7.5	N/A
	Single Unit	41x68, 49x48, 45x60, 33x96	LC50 optional some sizes	7.5	< 0.1
Clad Double-Hung Fixed	Single Unit	77x92	LC35 standard all sizes	5.25	< 0.1
	Single Unit	50x68, 42x80	C50 optional some sizes	7.5	< 0.1
Clad Double-Hung Transom	Single Unit	77x48	LC35 standard all sizes	6	< 0.1
	Single Unit	37x48	LC50 optional all sizes	12	< 0.2
Clad Epic Double-Hung	Single Unit	56x129	R15 standard some sizes	2.9	< 0.2
	Single Unit	56x105	LC25 standard some sizes	5.25	< 0.3
Clad Epic Double-Hung Fixed	Single Unit	68x105 (also tested - 56x129)	C50 standard all sizes	7.5	< 0.1
Clad Gliding	XO	72x60	R35 standard all sizes	5.25	< 0.1
	XOX	96x60	R35 standard all sizes	5.25	< 0.1
Clad Direct-Set Geometric	Single Unit	84x84	R35 standard all sizes	12	< 0.1
	Single Unit	84x84	R50 option all sizes	12	< 0.1
Clad Stationary In-Sash Geometric	Single Unit	96x48	R65	12	< 0.1
Clad Out-Swing Patio Door	Single Unit	44x98	+/- 35 psf structural only	N/A	N/A
	Single Unit	38x98	+/- 50 psf structural only	N/A	N/A
	XO	76x98	+/- 35 psf structural only	N/A	N/A
	XOO	112x98	+/- 35 psf structural only	N/A	N/A
Clad Out-Swing French Patio Door	XX	75x98	R35	5.25	< 0.1
	XX	76x98	+/- 50 psf structural only	N/A	N/A
Clad Narrow Gliding Patio Door	2-Panel	99x99	R30	4.50	< 0.2
	3-Panel	150x99	R20	3.00	≤ 0.3
	4-panel	197x99	R20	3.00	≤ 0.3
Clad Wide Gliding Patio Door	2-Panel	99x99	R30 standard	4.50	< 0.2
	2-Panel	99x99	LC50 optional	7.50	< 0.2
	3-Panel	150x99	R20 standard	3.00	≤ 0.3
	3-Panel	114x111	R35	5.25	< 0.2
	3-Panel	150x110	R20	3.00	≤ 0.3
	4-panel	197x99	R20	3.00	≤ 0.3
	4-Panel	148x111	R25	3.75	< 0.2
Clad Inswing Patio Door	X	44x98	+/- 40 psf structural only	N/A	N/A
	X	38x98	+/- 45 psf structural only	N/A	N/A
	XO	75x98	+/- 35 psf structural only	N/A	N/A
	OXX	111x98	+/- 30 psf structural only	N/A	N/A
Clad In-Swing French Patio Door	XX	75x98	+/- 35 psf structural only	N/A	N/A

## Custom Primed Wood

Product	AAMA/WDMA				
	101 / I.S. 2 / A440-05				
	Config.	Max Size Tested	Hallmark Certified Performance Rating	Water Performance (psf)	Air Performance (cfm/ft <sup>2</sup> )
Primed Casement	Single Unit		C35 standard all sizes		
	Single Unit	36x84	C50 optional all sizes	12.00	< 0.2
	Single Unit	36x72	C65 optional some sizes		
Primed Radius Casement	Single Unit		C35 standard all sizes		
	Single Unit	30x84	C50 optional all sizes	12.00	< 0.3
Primed Casement Fixed	Single Unit		C35 standard all sizes		
	Single Unit	72x84	C50 optional all sizes	7.50	< 0.1
	Single Unit	60x72	C65 optional some sizes	9.50	< 0.1
Primed French Casement	Single Unit	46x72	R20 standard all sizes	3.00	< 0.3
	Single Unit	56x54	R30 standard some sizes	5.25	< 0.1
Primed Push-Out Casement	Single Unit	36x72	C50 standard all sizes	7.5	< 0.2
Primed Push-Out Casement Fixed	Single Unit	60x72	C80 standard all sizes	12	< 0.1
Primed Awning	Single Unit	60x48	C30 standard all sizes	9.75	< 0.1
	Single Unit	48x36	C50 optional some sizes	9.75	< 0.1
	Single Unit	36x24	C65 optional some sizes	9.75	< 0.1
Primed Double-Hung	Single Unit	38x80	LC40 optional all sizes	5.25	< 0.3
	Single Unit	50x48, 36x72, 42x68, 45x60	LC50 optional some sizes	7.50	< 0.1
Primed Double-Hung Fixed	Single Unit	77x92	R20 standard all sizes	3.00	< 0.1
	Single Unit	77x92	LC35 optional all sizes	5.25	< 0.1
Primed Double-Hung Transom	Single Unit		LC35 standard all sizes		
	Single Unit	78x48	LC50 optional all sizes	7.50	< 0.1
Primed Epic Double-Hung	Single Unit	68x105	R15 standard some sizes	2.90	≤ 0.2
Primed Gliding	XO	72x60	C35 standard all sizes	5.25	< 0.2
Primed Direct-Set Geometric	Single Unit		R35 standard all sizes		
	Single Unit		R50 option all sizes		
	Single Unit	84x84	R65 optional all sizes	12.00	< 0.1
Primed Insash Geometric	Single Unit	96x48	R65 standard all sizes	9.75	< 0.1
Primed Out-Swing Patio Door	Single Unit	44x98	R30	4.50	< 0.2
	Single Unit	44x97	+/- 50 psf structural only	N/A	N/A
	Single Unit	38x98	+/- 75 psf structural only	N/A	N/A
	XOO	111x98	+/- 30 psf structural only	N/A	N/A
Primed Out-Swing French Patio Door	XX	74x98	+/- 20 psf structural only	N/A	N/A
Primed Narrow Gliding Patio Door	2-Panel	75x99	R40	6.00	< 0.2
	2-Panel	99x99	R30	4.50	< 0.2
	3-Panel	150x99	R20	3.00	< 0.2
	4-Panel	196x99	R20	3.00	< 0.3
Primed Wide Gliding Patio Door	2-Panel	75x99	R40	6.00	< 0.2
	3-Panel	150x111	R20	3.00	< 0.2
	4-Panel	150x111	R20	3.00	< 0.2
Primed Inswing Patio Door	X	44x97	+/- 50 psf structural only	N/A	N/A
	XO	74x98	+/- 75 psf structural only	N/A	N/A
Primed In-Swing French Patio Door	XX	75x98	+/- 30 psf structural only	N/A	N/A

Rev. 05/29/09

RELIABILITY *for real life*®

