

The performance information listed is intended to be used for reference only and is not complete. Depending on the components, accessories, and options chosen, the actual rating could vary. Confirm ratings for specific products with your supplier or JELD-WEN sales representative.

Product	AAMA/WDMA				
	101 / I.S. 2 / A440-05				
	Config.	Max Size Tested	Hallmark Certified Performance Rating (DP)	Water Performance (psf)	Air Performance (cfm/ft2)
Clad Casement	Single Unit	30x78	LC35 standard all sizes	5.25	< 0.1
	Single Unit	36x72, 24x84, 30x77	LC50 optional some sizes	7.52	< 0.1
	Single Unit	24x84, 36x72	LC60 optional some sizes	9.00	< 0.1
	Twin	48x84	LC35	5.25	< 0.1
	Twin	48x84	LC50 option	7.52	< 0.1
	Twin XO	60x84	LC60 optional some sizes	9.00	< 0.1
Clad Casement Picture	Single Unit	84x84	LC35 standard all sizes	5.25	< 0.1
	Single Unit	72x72	LC50 optional some sizes	7.52	< 0.1
	Single Unit	48x84	LC60 optional some sizes	9.00	< 0.1
Clad Awning	Single Unit	48x48 (also tested - 60x36)	LC35 standard all sizes	5.25	< 0.1
	Single Unit	48x48	LC50 optional some sizes	7.52	< 0.1
Clad Double-Hung	Single Unit	45x92	LC35 standard all sizes	5.25	< 0.1
	Single Unit	45x80	LC50 optional some sizes	7.52	< 0.1
	Single Unit	41x64	LC60 optional some sizes	9.00	< 0.1
	Twin	91x92	LC35	5.25	< 0.1
	Triple	112x64	LC50 optional	7.52	< 0.1
Clad Double-Hung Picture	Single Unit		LC35 standard	5.25	< 0.1
	Single Unit	77x88 (also tested - 49x92)	LC50 optional	7.52	< 0.1
Clad Direct-Set Radius	Single Unit	84x84	LC35	5.25	< 0.1
	Single Unit	68x68	LC50 standard - sizes $\leq$ 32 sq. ft.	7.52	< 0.1
Clad 400 series Sliding Patio Door	XO	96x96	C35 standard	5.25	< 0.1
	XO	72x95.5	C50 optional	7.52	< 0.1
Clad 400 series Sliding Patio Door Sidelight	O	52x96	C35 standard	5.25	< 0.1
	O	39.5x95.5	C50 optional	7.52	< 0.1
Clad 300 series Sliding Patio Door	XO	96x96	LC25 standard	3.75	< 0.1
	XO	72x95.5	LC50 optional	7.52	< 0.1
Clad 300 series Sliding Patio Door Sidelight	O	38.75x95.5	LC50	7.52	< 0.1
Clad Outswing Patio Door	X	36x96	SHED 50	N/A	N/A
Clad Stationary Outswing Patio Door	O	36x96	SHED 50	N/A	N/A
Clad Outswing Patio Door	XO	77x95.5	SHED 50	N/A	N/A

## Siteline EX Primed Wood

Product	AAMA/WDMA				
	101 / I.S. 2 / A440-05				
	Config.	Max Size Tested	Hallmark Certified Performance Rating (DP)	Water Performance (psf)	Air Performance (cfm/ft2)
Primed Casement	Single Unit	24x84	LC35 standard	5.25	< 0.1
	Single Unit	36x72, 30x78, 24x84	LC50 optional some sizes	7.52	< 0.1
Primed Casement Picture	Single Unit	84x84	LC35 standard all sizes	5.25	< 0.1
	Single Unit	72x72	LC50 optional some sizes	7.52	< 0.1
Primed Awning	Single Unit	48x48 (also tested - 60x36)	LC35 standard all sizes	5.25	< 0.1
	Single Unit	48x48	LC50 optional	7.50	< 0.1
Primed Double-Hung	Single Unit	45x92	LC35 standard all sizes	5.25	< 0.1
	Single Unit	45x60, 33x80	LC50 optional some sizes	7.52	< 0.1
Primed Double-Hung Fixed	Single Unit	77x88	LC35 standard all sizes	5.25	< 0.1
	Single Unit	50x92	LC50 optional some sizes	7.52	< 0.1

Rev. 4/30/09

RELIABILITY *for real life*®

